

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY****1.1 PRODUCT IDENTIFIER**

Product form: Mixture
Trade name: FIX607 Duct Sealant
Product code: FIX607
Type of product: Adhesives, Sealants
Product group: Trade product

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

1.2.1.
Relevant identified uses: Intended for general public.

1.2.2.
Uses advised against: No additional information available

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Company Name: Allfasteners USA LLC
480 Meadow Lane
Carlstadt, NJ 07072
United States

Telephone: 201.783.8836

Fax: 201.783.8840

Email: salesny@allfasteners.com

1.4 EMERGENCY PHONE NUMBER

Emergency Telephone: 1.800.577.3171

SECTION 2: HAZARDOUS IDENTIFICATION**2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE**

Classification according to Regulation (EC) No. 1272/2008 [CLP]Mixture/Substance: SDS EU 2015: According to Regulation (EU) 2015/830 (REACH Annex II)

**Reproductive toxicity,
Additional category,
Effects on or via lactation:** H362 Calculation method

Full text of hazard classes and H-statements : see section 16

**Hazardous to the aquatic
environment –
Chronic Hazard, Category 2:** H411 Calculation method

**Adverse physicochemical,
human health and
environmental effects:** May cause harm to breast-fed children. Toxic to aquatic life with long lasting effects.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**2.2 LABEL ELEMENTS**

Labeling according to Regulation (EC) No. 1272/2008 [CLP] Extra

Hazard pictograms (CLP):



GHS09

Signal word (CLP):

-

Hazardous ingredients: alkanes, C14-17, chloro, chlorinated paraffins, C14-17

Hazard statements (CLP): H362 - May cause harm to breast-fed children
H411 - Toxic to aquatic life with long lasting effectsPrecautionary statements (CLP): P201 - Obtain special instructions before use
P260 - Do not breathe dust, fume, gas, mist, spray, vapors
P263 - Avoid contact during pregnancy/while nursing
P273 - Avoid release to the environment
P308+P313 - IF exposed or concerned: Get medical advice/attention
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

EUH-statements: EUH066 - Repeated exposure may cause skin dryness or cracking

Child-resistant fastening: Not applicable

Tactile warning: Not applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 SUBSTANCE**

Not applicable

3.2 MIXTURE

NAME	PRODUCT IDENTIFIER	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
alkanes, C14-17, chloro, chlorinated paraffins, C14-17	(CAS No) 85535-85-9 (EC no) 287-477-0 (EC index no) 602-095-00-X	1 - 10	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
ethanediol, ethylene glycol	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	1 - 5	Acute Tox. 4 (Oral), H302

Full text of H-statements: see section 16.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**SECTION 4: FIRST AID MEASURES****4.1 DESCRIPTION OF FIRST AID MEASURES**

General:	IF exposed or concerned: Get medical advice/attention.
Inhalation:	Remove person to fresh air and keep comfortable for breathing.
Skin contact:	Wash skin with plenty of water.
Eye contact:	Rinse eyes with water as a precaution.
Ingestion:	Call a poison center or a doctor if you feel unwell.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Symptoms/injuries after skin contact:	Repeated exposure may cause skin dryness or cracking.
--	---

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 EXTINGUISHING MEDIA**

Suitable extinguishing media: Water spray. Dry powder. Foam.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous decomposition products in case of fire: Toxic fumes may be released.

5.3 ADVICE FOR FIRE-FIGHTERS

Protection during firefighting: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES****6.1.1. For non-emergency personnel**

Emergency procedures: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapors/spray.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES CONTINUED****6.1.2. For emergency responders**

Protective equipment Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2 ENVIRONMENTAL PRECAUTIONS

Avoid release to the environment.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

For containment: Collect spillage.

Methods for cleaning up: Recover mechanically the product.

Other information: Dispose of materials or solid residues at an authorized site.

6.4 REFERENCE TO OTHER SECTIONS

For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE**7.1 PRECAUTIONS FOR SAFE HANDLING**

Precautions for safe handling: Ensure good ventilation of the work station. Wear personal protective equipment. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not breathe dust/fume/gas/mist/vapors/spray.

Hygiene measures: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

6.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage conditions: Store in a well-ventilated place. Keep cool.

7.3 SPECIFIC END USE(S)

No additional information available.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 CONTROL PARAMETERS**

EU	Local name	Ethylene glycol
EU	IOELV TWA (mg/m ³)	52 mg/m ³
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m ³)	104 mg/m ³
EU	IOELV STEL (ppm)	40 ppm
EU	Notes	Skin
Austria	Local name	Ethylenglykol
Austria	MAK (mg/m ³)	26 mg/m ³
Austria	MAK (ppm)	10 ppm
Austria	MAK Short time value (mg/m ³)	52 mg/m ³
Austria	MAK Short time value (ppm)	20 ppm
Austria	Remark (AT)	H
Belgium	Local name	Ethylèneglycol (en aérosol)
Belgium	Limit value (mg/m ³)	52 mg/m ³
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m ³)	104 mg/m ³
Belgium	Short time value (ppm)	40 ppm
Belgium	Remark (BE)	D, M
Bulgaria	Local name	Етиленгликол•
Bulgaria	OEL TWA (mg/m ³)	52 mg/m ³
Bulgaria	OEL STEL (mg/m ³)	104 mg/m ³
Croatia	Local name	etandiol; (Etilenglikol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m ³)	52 mg/m ³
Croatia	GVI (granična vrijednost izloženosti) (ppm)	20 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m ³)	104 mg/m ³
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	40 ppm
Croatia	Naznake (HR)	K, EU* Xn
Czech Republic	Local name	Ethylenglykol
Czech Republic	Expoziční limity (PEL) (mg/m ³)	50 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	20 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	100 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	39 ppm
Czech Republic	Remark (CZ)	D
Estonia	Local name	1,2-etaandiool (etüleenglükool)
Estonia	OEL TWA (mg/m ³)	52 mg/m ³
Estonia	OEL TWA (ppm)	20 ppm
Estonia	OEL STEL (mg/m ³)	104 mg/m ³
Estonia	OEL STEL (ppm)	40 ppm
Finland	Local name	1,2-Etaanidioli
Finland	HTP-arvo (8h) (mg/m ³)	50 mg/m ³
Finland	HTP-arvo (8h) (ppm)	20 ppm

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**8.1 CONTROL PARAMETERS CONTINUED**

Finland	HTP-arvo (15 min)	100 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	40 ppm
France	Local name	Ethylèneglycol (vapeur)
France	VME (mg/m ³)	52 mg/m ³
France	VME (ppm)	20 ppm
France	VLE (mg/m ³)	104 mg/m ³
France	VLE (ppm)	40 ppm
Germany	Local name	Ethandiol
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	26 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	10 ppm
Germany	Remark (TRGS 900)	DFG,EU,H,Y
Greece	OEL TWA (mg/m ³)	125 mg/m ³
Greece	OEL TWA (ppm)	50 ppm
Greece	OEL STEL (mg/m ³)	125 mg/m ³
Greece	OEL STEL (ppm)	50 ppm
Hungary	Local name	ETILÉNGLIKOL
Hungary	AK-érték	52 mg/m ³
Hungary	CK-érték	104 mg/m ³
Hungary	Megjegyzések (HU)	b, i; I.
Italy	Local name	Etilen glicol
Italy	OEL TWA (mg/m ³)	52 mg/m ³
Italy	OEL TWA (ppm)	20 ppm
Italy	OEL STEL (mg/m ³)	104 mg/m ³
Italy	OEL STEL (ppm)	40 ppm
Latvia	Local name	Etilēnglikols, (1,2-etāndiols)
Latvia	OEL TWA (mg/m ³)	52 mg/m ³
Latvia	OEL TWA (ppm)	20 ppm
Latvia	OEL STEL (mg/m ³)	104 mg/m ³
Latvia	OEL STEL (ppm)	40 ppm
Lithuania	Local name	Etilenglikolis (1,2-etandiolis, glikolis)
Lithuania	IPRV (mg/m ³)	25 mg/m ³
Lithuania	IPRV (ppm)	10 ppm
Lithuania	TPRV (mg/m ³)	50 mg/m ³
Lithuania	TPRV (ppm)	20 ppm
Lithuania	Remark (LT)	0
Luxembourg	Local name	Ethylène-glycol
Luxembourg	OEL TWA (mg/m ³)	52 mg/m ³
Luxembourg	OEL TWA (ppm)	20 ppm
Luxembourg	OEL STEL (mg/m ³)	104 mg/m ³
Luxembourg	OEL STEL (ppm)	40 ppm
Malta	Local name	Ethylene glycol
Malta	OEL TWA (mg/m ³)	52 mg/m ³

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**8.1 CONTROL PARAMETERS CONTINUED**

Malta	OEL TWA (ppm)	20 ppm
Malta	OEL STEL (mg/m ³)	104 mg/m ³
Malta	OEL STEL (ppm)	40 ppm
Poland	Local name	Glikol etylenowy
Poland	NDS (mg/m ³)	15 mg/m ³
Poland	NDSCh (mg/m ³)	50 mg/m ³
Portugal	Local name	Etilenoglicol
Portugal	OEL - Ceilings (mg/m ³)	100 mg/m ³
Romania	Local name	Etilenglicol
Romania	OEL TWA (mg/m ³)	52 mg/m ³
Romania	OEL TWA (ppm)	20 ppm
Romania	OEL STEL (mg/m ³)	104 mg/m ³
Romania	OEL STEL (ppm)	40 ppm
Slovenia	Local name	etandiol (glikol)
Slovenia	OEL TWA (mg/m ³)	52 mg/m ³
Slovenia	OEL TWA (ppm)	20 ppm
Slovenia	OEL STEL (mg/m ³)	104 mg/m ³
Slovenia	OEL STEL (ppm)	40 ppm
Spain	Local name	Etilenglicol
Spain	VLA-ED (mg/m ³)	52 mg/m ³
Spain	VLA-ED (ppm)	20 ppm
Spain	VLA-EC (mg/m ³)	104 mg/m ³
Spain	VLA-EC (ppm)	40 ppm
Spain	Notes	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	Ethylene glycol
Sweden	nivågränsvärde (NVG) (mg/m ³)	25 mg/m ³
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm
Sweden	kortidsvärde (KTV) (mg/m ³)	50 mg/m ³
Sweden	kortidsvärde (KTV) (ppm)	20 ppm
United Kingdom	Local name	Ethane-1,2-diol

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**8.1 CONTROL PARAMETERS CONTINUED**

United Kingdom	WEL TWA (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
United Kingdom	WEL TWA (ppm)	20 ppm vapour
United Kingdom	WEL STEL (mg/m ³)	104 mg/m ³ vapour
United Kingdom	WEL STEL (ppm)	40 ppm vapour
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Switzerland	Local name	Ethylèneglycol
Switzerland	VME (mg/m ³)	26 mg/m ³
Switzerland	VME (ppm)	10 ppm
Switzerland	VLE (mg/m ³)	52 mg/m ³
Switzerland	VLE (ppm)	20 ppm
Switzerland	Remark (CH)	4x15
USA - ACGIH	Local name	Ethylene glycol
USA - ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA - ACGIH	Remark (ACGIH)	URT & eye irr

8.2 EXPOSURE CONTROLS

Appropriate engineering controls: Ensure good ventilation of the work station.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin and body protection: Wear suitable protective clothing.

Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls: Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

Physical state:	Solid	Relative evaporation rate (butyl acetate=1):	No data available.
Appearance:	Paste.	Melting point:	No data available.
Color:	Grey.	Freezing point:	Not applicable.
Odor:	Characteristic.	Boiling point:	No data available.
Odor threshold:	No data available.	Flash point:	Not applicable.
pH:	7.5 - 9	Auto-ignition temperature:	Not applicable.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES CONTINUED**

Decomposition temperature:	No data available.	Solubility:	No data available.
Flammability (solid, gas):	Non Flammable.	Log Pow:	No data available.
Vapor pressure:	No data available.	Viscosity, kinematic:	Not applicable.
Relative vapor density at 20 °C:	No data available.	Viscosity, dynamic:	No data available.
Relative density:	Not applicable.	Explosive properties:	No data available.
Density:	1.55 - 1.61 g/cm ³	Oxidizing properties:	No data available.
		Explosive limits:	Not applicable.

9.2 OTHER INFORMATION

VOC content: < 1 g/l

SECTION 10: STABILITY AND REACTIVITY**10.1 REACTIVITY**

The product is non-reactive under normal conditions of use, storage and transport.

10.2 CHEMICAL STABILITY

Stable under normal conditions.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reactions known under normal conditions of use.

10.4 CONDITIONS TO AVOID

None under recommended storage and handling conditions (see section 7).

10.5 INCOMPATIBLE MATERIALS

No additional information available.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

Acute toxicity:	Not classified.	Carcinogenicity:	Not classified.
Skin corrosion/irritation:	Not classified. pH: 7.5 - 9	Reproductive toxicity:	May cause harm to breast-fed children.
Serious eye damage/irritation:	Not classified. pH: 7.5 - 9	Specific target organ toxicity (single exposure):	Not classified.
Respiratory or skin sensitization:	Not classified.	Specific target organ toxicity (repeated exposure):	Not classified.
Germ cell mutagenicity:	Not classified.	Aspiration hazard:	Not classified.

SECTION 12: ECOLOGICAL INFORMATION**12.1 TOXICITY**

Ecology - general: Toxic to aquatic life with long lasting effects.

12.2 PERSISTENCE AND DEGRADABILITY

No additional information available.

12.3 BIOACCUMULATIVE POTENTIAL

No additional information available.

12.4 MOBILITY IN SOIL

No additional information available.

12.5 RESULTS OF PBT AND VPVB ASSESSMENT

No additional information available.

12.6 OTHER ADVERSE EFFECTS

No additional information available.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 WASTE TREATMENT METHODS**

Waste treatment methods: Dispose of contents/container in accordance with licensed collector's sorting instructions.

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**SECTION 14: TRANSPORT INFORMATION**

In accordance with ADR / RID / IMDG / IATA / ADN

14.1 UN NUMBER

UN-No. (ADR):	3077
UN-No. (IMDG):	3077
UN-No. (IATA):	3077
UN-No. (ADN):	3077
UN-No. (RID):	3077

14.2 UN PROPER SHIPPING NAME

Proper Shipping Name (ADR):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (IMDG):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (IATA):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (ADN):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (RID):	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Transport document description (ADR):	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, (E)
Transport document description (IMDG):	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA):	UN 3077 Environmentally hazardous substance, solid, n.o.s., 9, III, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN):	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID):	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS

14.3 TRANSPORT HAZARD CLASS(ES)

ADR		IMDG	
Transport hazard class(es) (ADR):	9	Transport hazard class(es) (IMDG):	9
Danger labels (ADR):	9	Danger labels (IMDG):	9





FIX607
INDUSTRIAL ACRYLIC DUCT SEALANT

14.3 TRANSPORT HAZARD CLASS(ES) CONTINUED

IATA

Transport hazard class(es) (IATA): 9
Danger labels (IATA): 9



RID

Transport hazard class(es) (RID): 9
Danger labels (RID): 9



ADN

Transport hazard class(es) (ADN): 9
Danger labels (ADN): 9



14.4 PACKING GROUP

Packing group (ADR):	III	Packing group (ADN):	III
Packing group (IMDG):	III	Packing group (RID):	III
Packing group (IATA):	III		

14.5 ENVIRONMENTAL HAZARDS

Dangerous for the environment: Yes
Marine pollutant: Yes
Other information: No supplementary information available

14.6 SPECIAL PRECAUTIONS FOR USER

- Overland transport

Classification code (ADR):	M7	Portable tank and bulk container instructions (ADR):	T1, BK1, BK2
Special provisions (ADR):	274, 335, 601, 375	Portable tank and bulk container special provisions (ADR):	TP33
Limited quantities (ADR):	5kg	Vehicle for tank carriage:	SGAV, LGBV
Excepted quantities (ADR):	E1	Transport category (ADR):	3
Packing instructions (ADR):	P002, IBC08, LP02, R001	Special provisions for carriage - Packages (ADR):	V13
Special packing provisions (ADR):	PP12, B3		
Mixed packing provisions (ADR):	MP10		

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**14.6 SPECIAL PRECAUTIONS FOR USER CONTINUED****- Overland transport (continued)**

Special provisions for carriage - Bulk (ADR): VC1, VC2

Special provisions for carriage - Loading, unloading and handling (ADR): CV13

Hazard identification number (Kemler No.): 90

Orange plates:



Tunnel restriction code (ADR): E

EAC code: 2Z

- Transport by sea

Special provisions (IMDG): 274, 335, 966, 967, 969

Limited quantities (IMDG): 5 kg

Excepted quantities (IMDG): E1

Packing instructions (IMDG): P002, LP02

Special packing provisions (IMDG): PP12

IBC packing instructions (IMDG): IBC08

IBC special provisions (IMDG): B3

Tank instructions (IMDG): T1, BK1, BK2, BK3

Tank special provisions (IMDG): TP33

EmS-No. (Fire): F-A

EmS-No. (Spillage): S-F

Stowage category (IMDG): A

Stowage and handling (IMDG): SW23

MFAG-No: 171

- Air transport

PCA Excepted quantities (IATA): E1

PCA Limited quantities (IATA): Y956

PCA limited quantity max net quantity (IATA): 30kgG

PCA packing instructions (IATA): 956

PCA max net quantity (IATA): 400kg

CAO packing instructions (IATA): 956

CAO max net quantity (IATA): 400kg

Special provisions (IATA): A97, A158, A179, A197

ERG code (IATA): 9L

- Inland waterway transport

Classification code (ADN): M7

Special provisions (ADN): 274, 335, 375, 601

Limited quantities (ADN): 5 kg

Excepted quantities (ADN): E1

Carriage permitted (ADN): T* B**

Equipment required (ADN): PP, A

Number of blue cones/lights (ADN): 0

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**14.6 SPECIAL PRECAUTIONS FOR USER CONTINUED**

- Rail transport

Classification code (RID):	M7	Transport category (RID):	3
Special provisions (RID):	274, 335, 375, 601	Special provisions for carriage – Packages (RID):	W13
Limited quantities (RID):	5kg	Special provisions for carriage – Bulk (RID):	VC1, VC2
Excepted quantities (RID):	E1	Special provisions for carriage - Loading, unloading and handling (RID):	CW13, CW31
Packing instructions (RID):	P002, IBC08, LP02, R001	Colis express (express parcels) (RID):	CE11
Special packing provisions (RID):	PP12, B3	Hazard identification number (RID):	90
Mixed packing provisions (RID):	MP10		
Portable tank and bulk container instructions (RID):	T1, BK1, BK2		
Portable tank and bulk container special provisions (RID):	TP33		
Tank codes for RID tanks (RID):	SGAV, LGBV		

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE****15.1.1. EU-Regulations****VOC content:** < 1 g/l

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations**Germany**

VwVwS Annex reference:

Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV:

Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

**FIX607**
INDUSTRIAL ACRYLIC DUCT SEALANT**15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS... CONTINUED****15.1.2. National regulations continued****Netherlands**

SZW-lijst van kankerverwekkende stoffen:	alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed
SZW-lijst van mutagene stoffen:	alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding:	alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid:	None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling:	None of the components are listed

Denmark

Classification remarks:	Emergency management guidelines for the storage of flammable liquids must be followed.
Recommendations Danish Regulation:	Pregnant/breastfeeding women working with the product must not be in direct contact with the product.

15.2 CHEMICAL SAFETY ASSESSMENT

No chemical safety assessment has been carried out

SECTION 16: OTHER INFORMATION

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
H302	Harmful if swallowed
H362	May cause harm to breast-fed children
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product



FIX607
INDUSTRIAL ACRYLIC DUCT SEALANT

16.1 HISTORY

Date of issue: 3/16/2015
Revision date: 1/12/2016
Supersedes: 3/16/2015
Version: 1.0

16.2 DISCLAIMER

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product